




Pressing Unit ACO153

Compact and highperformance efficiency

NEW with rotatable head



- Redundant switch-off and press force control with LED indication
- Automatic pressing cycle
- Safe handling with slipproof rubberized housing and ergonomic design
- Illumination of the press area for safe working
- Analysis of the pressing tool performance via NovoCheck app



Press jaw PB15



Pressing Unit ACO153

Compact and high-performance efficiency

The pressing unit ACO153 has many valuable features to make working easier, faster and safer. The LED signal located under the transparent start button gives information about the battery and the status of the pressing unit or occurred failures. Thanks to the implemented Bluetooth®-Technology, device-related data can be requested via the NovoCheck app.

NovoCheck-App

- Data transfer between pressing tool and app
- Possibility to check the pressing tool's current status
- Analysis of the pressing tool performance
- Integrated report function for documentation of the installation



Scope of application

- Drinking water-, gas- and heating installations, industry and commercial applications and many more
- Suitable for all authorized jaws of other system manufacturers in the market¹
- All common profiles for metal and plastic systems available

Accessories

- Press jaws PB15
- Charger available in many worldwide power supply specifications
- Batteries with different capacities available

The LED signal located under the transparent start button gives information about the battery and the status of the pressing units or occurred failures.



Novopress quality and service

Tool features

- Battery-empty-detection
- Error display
- Device information through the LED indication under the start button
- Automatic pressing cycle
- Electronic bolt retention

Maintenance and service


- Qualified service on site thanks to international service network
- Extended warranty (further information at www.novopress.de)



Dimensions ² :	Metal pipe up to 32 mm (Australian standard)/
	Plastic pipe up to 40 mm
Weight without battery:	1.6 kg
Length:	320 mm
Width:	98 mm
Height:	72 mm
Power consumption:	240 W
Piston force:	24 kN
Piston stroke:	30 mm
Battery:	Milwaukee® M12™ battery system³
Battery capacity⁴:	up to 250 pressing cycles
Charging time ⁵ :	45 - 75 Min.

- 1 for binding information please request your system manufacturer
- 2 system-dependant
- 3 all Milwaukee® capacities in the market can be used
- 4 depending on material, dimension and battery capacity

5 depending on battery capacity



www.novopress.de · E-Mail: verkauf@novopress.de